AFRICAN UNION الاتحاد الأفريقي



UNION AFRICAINE UNIÃO AFRICANA

AFRICAN COURT ON HUMAN AND PEOPLES' RIGHTS COUR AFRICAINE DES DROITS DE L'HOMME ET DES PEUPLES

P.O Box 6274 Arusha, Tanzania, Tel: +255 732 979506/9; Fax: +255 732 979503

Ref: AfCHPR/TBC/2017/87

Date: 20th June 2017

TO: ALL INTERESTED SUPPLIERS

REQUEST FOR QUOTATIONS (RFQ) FOR MULTI-FUNCTIONAL PRINTERS

BACKGROUND:

The African Court on Human and Peoples' Rights (AfCHPR) whose headquarters is located in Arusha, Tanzania is an Organ of the African Union. In its effort to carry out its mandate, the Court would like to procure Multi-Functional Printers (See table overleaf for specification), and hereby invites interested and qualified Suppliers to submit their priced quotations in Tanzanian Shillings.

TERMS AND CONDITIONS:

Interested suppliers should submit in their Proforma Invoices for supply of the required items and submit them by hand immediately after received this Request for Quotation and not later than 17:00hrs on 27th June 2017.

The sealed envelopes should be deposited in the Office of Procurement, Travel and Stores services, of the African Court situated at TANAPA, Mwalimu Julius Nyerere Conservancy Centre, Phase II, Dodoma Road. The focal point is Mr. Alex Naing'olah Mollel, Procurement, Travel and Stores Assistant.

Email: procurement@african-court.org

You are hereby requested to make an offer only if you can supply the items within the terms and conditions stipulated, and within the prescribed dates.



The African Court on Human and Peoples' Rights will not in any way be obliged to accept the lowest priced quotation, or any low prices as quality of the items supplied shall be one of the major considerations.

The African Court on Human and Peoples' Rights reserves the right to reject any offer without offering any reason thereto, to waive any defect or informality therein, and to award any Supplier whose offer is deemed most advantageous to the Court without incurring any liability whatsoever to the losing Supplier who may be adversely affected by such award or rejection.

The Court assumes no obligation for whatever expenses or losses that may be incurred by any Supplier in the preparation of the request for quotation, nor does it guarantee that an award shall be made.

DETAILS OF THE REQUIRED ITEMS:

Category I: SPECIFICATIONS FOR B&W MULTI-FUNCTIONAL PRINTER

Specifications For Blank	and White Multi-Funct	ional Printer
Warm up time:		20 seconds
First output speed: Continuous output speed:		6 seconds 25 seconds
	Maximum:	1.5 GB
HDD:	Option:	250 GB
Dimensions (WxDxH):		587 x 568 x 558 mm
Weight:		44 kg
Power source:		220-240 V, 50/60 Hz
COPIER		
Copying process:		Laser beam scanning & electro photographic printing
Multiple copying:		Up to 999 copies

Resolution:		600 dpi
Zoom:		From 25% to 400%
PRINTER		
Printer language:	Standard:	PCL5e, PCL6, RPCS™
	Option:	Adobe® PostScript® 3™
Resolution:		600 x 600 dpi
Interface:	Standard:	USB 2.0, SD slot, USB Host I/F, Ethernet 10 base-T/100 base- TX, Ethernet 1000 Base-T
	Option:	Bi-directional IEEE 1284,Wireless LAN (IEEE 802.11a/b/g), Bluetoot
Network protocol:		TCP/IP (IP v4, IP v6), IPX/SPX
Windows® environments:		Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:		Macintosh OS X v10.5 or later
UNIX environments:	UNIX Sun® Solaris:	2.6, 2.7, 2.8, 2.9, 2.10
	HP-UX:	10.x, 11.x, 11i v2, 11i v3,
	SCO OpenServer:	5.0.6, 5.0.7, 6.0
	RedHat® Linux Enterprise:	4, 5, 6
	IBM® AIX:	5L v5.3, 5L v6.1, 5Lv7.1
		IBM® System i5™ HPT
Novell® Netware® environments:		v6.5
SAP® R/3® environments:		SAP® R/3.x or later
		mySAP ERP 2004 or later
Citrix environments:		Citrix Presentation Server 4.0, 4.5
		Xen App 5.6, 6.0, 6.5

Scan speed:	Full colour:	Maximum 50 originals per minute
	B/W:	Maximum 50 originals per minute
Resolution:	Maximum:	600 dpi, 1200 dpi (TWAIN)
Original size:		A3, A4, A5
File format:		TIFF, JPEG, PDF, Encrypt PDF, High compression PDF, PDF-A
Bundled drivers:		Network TWAIN, Scanner utility
Scan to:		E-mail, Folder, USB/SD, URL, WSD Scanner
FAX (OPTION)	4	
Circuit:		PSTN, PBX
Compatibility:		ITU-T (CCITT) G3
Resolution:		8 x 3.85 line/mm, 200 x 100dpi
		8 x 7.7 line/mm, 200 x 200dpi
Transmission speed:	G3:	Approx 2 seconds (200 x 100dpi, JBIG)
		Approx 3 seconds (200 x 100dpi)
Modem speed	Maximum:	33.6 Kbps
Scanning speed:		2 second(s)
Memory capacity:	Standard:	4 MB
PAPER HANDLING	£	*
Recommended paper size:	Paper tray(s):	A5 - A3
	Bypass tray:	A6 - A3
Paper input capacity:	Standard:	2 x 500-sheet paper trays
	Maximum:	3,100 sheets
Paper output capacity:	Standard:	350/600 sheets
	Maximum:	1,350/1,600 sheets
Paper weight:	Standard paper tray(s):	60-105 g/m²



	Bypass tray :	60-162 g/m²
	Duplex:	64-90 g/m²
ECOLOGY		
Power consumption:	Maximum:	1.55 kW
	Ready mode:	113W
	Sleep mode:	0.6 W
	TEC (Typical Electricity Consumption):	892/1,082 W/h
SOFTWARE		
Standard:		Smart Device Monitor,
		Web Smart Device Monitor
		Web Image Monitor
		Global Scan NX, Card Authentication Package

OPTIONS

ADF handle, Platen cover, ARDF, 1 x 500-sheet paper tray, 2 x 500-sheet paper tray, Onebin tray, Hard disk drive, RAM, VM card, Netware, Browser unit, Adobe® PostScript® 3™ option, Counter interface, File format converter, Copy data security unit, Wireless LAN (IEEE 802.11a/g), IEEE 1284, Bluetooth, Fax option, Fax connection unit, Fax marker

Category II: Specifications for Colour Multi-Functional Printer

Warm up time:	•	66 seconds
First output speed:	Full colour:	
r not output speed.		10.5 seconds
	B/W:	6.2 seconds
Continuous output speed:	Full colour:	35 pages per minute
	B/W:	40 pages per minute
Memory:		2 GB (Standard)
HDD:		320 GB
Dimensions (W x D x H):		510 x 588 x 505 mm
Weight:		45 kg
Power source:		220 - 240 V, 50/60 Hz
COPIER		
Copying process:		Dry electrostatic transfer system with Dual component Development 4-Drum method
Multiple copying:		Up to 99 copies
Resolution:		600 x 600 dpi
Zoom:		From 25% to 400% in 1% steps
PRINTER		
Printer language:	Standard:	PCL5c, PCL6(XL), PDF, Adobe® PostScript® 3™,
	Option:	XPS
Print resolution:	Maximum:	1,200 x 1,200 dpi
Interface:	Standard:	USB 2.0 Type A, USB 2.0 Type B, SD slot, Ethernet 10 base-T/100 base-TX, Ethernet 1000 base-T
	Option:	Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth
Network protocol:	TCP/IP: IP v4, IP v6	

Windows® environments:		Windows® Vista, Windows® 7, Windows® 8, Windows® 8.1, Windows® Server 2003, Windows® Server 2003R2, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012, Windows® Server 2012R2
Mac OS environments:		Macintosh OS X v10.7 or later
UNIX environments:		UNIX Sun® Solaris, HP-UX, SCO OpenServer, Red Hat® Linux, IBM® AIX
SAP® R/3® environments: Other supported environments:		SAP® R/3 3.x® or later NDPS Gateway, AS/400® using OS/400 Host Print Transform, IBM iSeries
Scanning speed:		Maximum 30 originals per minute
		(200dpi Full Color and B/W simplex)
Resolution:	Standard:	100 - 600 dpi
	Default:	200 dpi
Original size:		A4
File formats:		TIFF, JPEG, PDF, Encryption PDF, High Compression PDF, PDF-A
Bundled drivers:		Network TWAIN
Scan to:		E-mail, Folder, USB/SD, URL
FAX (OPTION)		· ·
Circuit:		PSTN, PBX
Compatibility:		ITU-T (CCITT) G3
Resolution:		8 x 3.85 line/mm, 200 x 100 dpi
		8 x 7.7 line/mm, 200 x 200 dpi
Compression method:		MH, MR, MMR, JBIG
Transmission speed G3:		2 second(s) (200 x 100 dpi, JBIG),



		3 second(s) (200 x 100 dpi, MMR
Modem speed	Maximum:	33.6 Kbps
Memory capacity:		41B
PAPER HANDLING		
Paper size:	Standard paper tray(s):	A4, A5, B5
	Bypass tray:	A4, A5, A6, B5, B6
Paper input capacity:	Standard:	350 sheets
	Maximum:	1,350 sheets
Paper output capacity:	Standard:	100 sheets
	Maximum:	200 sheets
Paper weight:	Paper tray(s):	60 - 163 g/m²
	Bypass tray:	60 - 220 g/m²
	Duplex tray:	60 - 163 g/m²
ECOLOGY		
Power consumption	Maximum:	1,200 W
	Ready mode:	51.9 W
	Sleep mode:	0.75 W
	TEC (Typical Electricity Consumption):	1,584 Wh

SOFTWARE (OPTION)

GlobalScan NX, Device Manager NX, Enhanced Locked Printed NX, Streamline NX, Card Authentication Package.

OPTIONS

Paper tray (500-sheet paper tray), One-bin tray, Bi-directional IEEEE 1284, USB Server for Second Network Interface, Bluetooth, Netware, Pictbridge, Counter interface, File format converter, Data Overwrite Security Unit (Certified version), Copy Data Security Unit, Fax Connection Unit, Unicode Font Package for SAP, Wireless LAN (IEEE 802.11a/g/n), OCR Unit, XPS direct print, NFC Card Reader



LOCATION OF DELIVERY:

The Headquarters of the African Court on Human and Peoples' Rights, situated at TANAPA, Mwalimu Julius Nyerere Conservancy Centre, Phase II, Dodoma Road.

FINANCIAL INFORMATION:

Suppliers' should provide a separate quotation for the transportation or delivery charges for the items to the Court, if any. Supplies should also indicate actual time of delivery of the items and mode of payment.

Sincerely,

Dr. Robert Eno

Registrar of the Court

CHE DES DEOL